

## TUNDRA



474




475



476



478



479



996-EC



996-EF

## TUNDRA

### EN

Composition: 42% Viscose, 38% Cotton, 14% Poly acrylic, 6% Polyester  
Maintenance: Vacuum regularly or professional Dry-clean  
Abrasion Resistance: 30.000 Martindale cycles  
Flammability: EN 1021 part 1&2

### DE

Zusammensetzung: 42% Viscose, 38% Baumwolle, 14% Poly Akryl, 6% Polyester  
Reinigung: Regelmässig staubsaugen. Professionelle Trockenreinigung  
Scheuerfestigkeit: 30.000 Martindale  
Feuerschutz: EN 1021 part 1&2

### FR

Composition: 42% Viscose, 38% Coton, 14% Poly acryl, 6% Polyester  
Nettoyage: Aspirer régulièrement. Nettoyage á sec professionnel  
Résistance á l'abrasion: 30.000 cycles Martindale  
Normes au feu: EN 1021 part 1&2

### DK

Materiale: 42% Viscose, 38% Bomuld, 14% Poly akryl, 6% Polyester  
Rengøring: Støvsug regelmæssigt eller professionel rens  
Slidstyrke: 30.000 Martindale  
Flammesikring: EN 1021 part 1&2